

Industrial Drilling Machines - Belt Drive



Industrial Drilling Machine Range

- Quality Casting, Construction & Componentry
- Emergency Stop
- NVR Safety Switch

Each Unit Supplied With

- Chuck Safety Guard
- Drill Chuck
- Drill Drift (on MT models)

Bench Drill Press



Part Number	TD0813	TD1013	TD1316	TD1416
Description	Bench Drill	Bench Drill	Bench Drill	Bench Drill
Max Drilling Cap.(mm)	13mm (1/2")	13mm (1/2")	16mm(5/8")	16mm(5/8")
Chuck Capacity	1.5-13mm	1.5-13mm	3-16mm	3-16mm
Motor Power	250W	375W	375W	450W
Spindle Travel(mm)	50	65	85	85
Number of Speeds	5	5	16	16
Speed Range(rpm)	620-2620	620-2620	180-2770	180-2770
Spindle Taper	B16	B16	MT#2	MT#2
Swing(mm)	210	260	325	360
Table Size(mm)	160*160	200*200	Φ290	290*290
Base Size(mm)	290*190	340*210	420*250	460*272
Column Dia.(mm)	φ46	Φ58	Φ70-72	Φ70-72
Height(mm)	580	680	980	1000
N.W./G.W.(kgs)	19/20	27/29	50/52	60/63
Packing Size(mm)	430x350x260	570x410x265	780x450x280	825x490x 290



Pedestal Drill Press

Part Number	TD1316F	TD1416F	TD1420F	TD1825F	TD2032F
Description	Pedestal Drill	Pedestal Drill	Pedestal Drill	Pedestal Drill	Pedestal Drill
Max Drilling Cap.(mm)	16mm(5/8")	16mm(5/8")	20mm(3/4")	25mm(1")	32mm(1-1/4")
Chuck Capacity	3-16mm	3-16mm	5-20mm	5-20mm	5-20mm
Motor Power	550W	550W	750W	1500W	1500W
Spindle Travel(mm)	85	85	85	120	120
Number of Speeds	16	16	12	12	12
Speed Range	180-2770	180-2770	280-2380	150-2450	150-2450
Spindle Taper	MT#2	MT#2	MT#3	MT#3	MT#4
Swing(mm)	325	360	360	450	510
Table Size(mm)	Φ290	290*290	290*290	350x350	420x480
Base Size(mm)	460*272	460*272	460*272	500x375	560x450
Column Dia.(mm)	Φ70-72	Φ70-72	Φ80	Φ92	Φ92
Height(mm)	1580	1600	1600	1710	1710
N.W./G.W.(kgs)	60/63	70/74	80/84	120/128	145/153
Packing Size(mm)	1140x460x280	1140x500x300	1140x500x300	1430x670x330	1430x670x330