acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 29, 2017 Revision: November 29, 2017

1 Identification

· Product identifier

· Trade name: Tap Magic Aluminum Liquid

· Other means of identification: No other identifiers

· Recommended use and restriction on use

· Recommended use: Machining, Cutting, Tapping, and Metal Processing.

· Restrictions on use:

After use of this product, clean and lubricate metal surfaces to avoid staining and/or corrosion.

Details of the supplier of the Safety Data Sheet

· Manufacturer/Supplier:

The Steco Corporation 2330 Cantrell Road Little Rock, AR 72203 USA (501) 375-5644

· Emergency telephone number:

ChemTel Inc. (800)255-3924 (North America) +1 (813)248-0585 (International)

Australian distributor

INDUSTRIAL TOOL & MACHINERY SALES Address 18 Business St, Yatala QLD 4207 Telephone (07) 3287 1114 sales@industrialtool.com.a

Australian emergency telephone number

Poisons Information Centre 131126 (AH)

(03) 9336 7945 (AH)

2 Hazard(s) identification

Classification of the substance or mixture

Skin Sens. 1 H317 May cause an allergic skin reaction.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · Label elements
- · GHS label elements

This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission. GHS labeling is not required per 29CFR1910.1200(b)(5)(v). The labeling below applies to industrial/professional products.

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:





GHS07 GHS08

· Signal word: Danger

Hazard statements:

H317 May cause an allergic skin reaction.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements:

P261 Avoid breathing mist, vapors, or spray.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection. P301+P310 If swallowed: Immediately call a poison center/doctor.

P302+P352 If on skin: Wash with plenty of soap and water.

P331 Do NOT induce vomiting.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

(Cont'd. on page 2)

Page: 2/9

(Cont'd. of page 1)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 29, 2017 Revision: November 29, 2017

Trade name: Tap Magic Aluminum Liquid

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· NFPA ratings (scale 0 - 4)



Health = 2 Fire = 1

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



2 Health = 2

1 Fire = 1

Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:			
64742-47-8	Distillates (petroleum), hydrotreated light	50-75%	
	♦ Asp. Tox. 1, H304		
111-82-0	Aliphatic Organic Ester	30-50%	
104-55-2	Cinnamal	<1%	
	① Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317		

Additional information:

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

- Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Wash with soap and water.

If skin irritation is experienced, consult a doctor.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

- Most important symptoms and effects, both acute and delayed: Allergic reactions
- · **Danger:** May be fatal if swallowed and enters airways.
- Indication of any immediate medical attention and special treatment needed:

(Cont'd. on page 3)

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 29, 2017 Revision: November 29, 2017

Trade name: Tap Magic Aluminum Liquid

(Cont'd. of page 2)

Contains Cinnamal. May produce an allergic reaction.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

If necessary oxygen respiration treatment.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Water fog / haze

Foam

Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water stream.
- Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Use personal protective equipment as required.

For large spills, wear protective clothing.

For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.

Environmental precautions

Do not allow to enter sewers/ surface or ground water.

Prevent from spreading (e.g. by damming-in or oil barriers).

Inform respective authorities in case of seepage into water course or sewage system.

· Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Remove from the water surface (e.g. skim or suck off).

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- ·Handling
- · Precautions for safe handling:

Use only in well ventilated areas.

Keep out of reach of children.

Avoid breathing mist, vapors, or spray.

(Cont'd. on page 4)

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 29, 2017 Revision: November 29, 2017

Trade name: Tap Magic Aluminum Liquid

(Cont'd. of page 3)

- Information about protection against explosions and fires: No special measures required.
- Conditions for safe storage, including any incompatibilities
- Storage
- Requirements to be met by storerooms and receptacles:

Store in cool, dry conditions in well sealed receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

· Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

64742-47-8 Distillates (petroleum), hydrotreated light

EL (Canada) Long-term value: 200 mg/m³

Skin

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Avoid close or long term contact with the skin.

Avoid contact with the eyes.

- · Engineering controls: Provide adequate ventilation.
- · Breathing equipment:

Not required under normal conditions of use.

Use suitable respiratory protective device in case of insufficient ventilation.

· Protection of hands:

Gloves are advised for repeated or prolonged contact.

Wear protective gloves to handle contents of damaged or leaking units.

- Eye protection: Follow relevant national guidelines concerning the use of protective eyewear.
- · Body protection: Protection may be required for spills.
- Limitation and supervision of exposure into the environment

No relevant information available.

9 Physical and chemical properties

Information on basic physical and chemical properties

· Appearance:

Form: Liquid
Color: Light yellow
Odor: Pleasant

(Cont'd. on page 5)

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 29, 2017 Revision: November 29, 2017

Trade name: Tap Magic Aluminum Liquid

		(Cont'd. of page 4
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Melting point/Melting range:	Not determined.	
Boiling point/Boiling range:	Not determined.	
Flash point:	>93 °C (>199.4 °F)	
Flammability (solid, gaseous):	Not applicable.	
Auto-ignition temperature:	Not determined.	
Decomposition temperature:	Not determined.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits		
Lower:	Not determined.	
Upper:	Not determined.	
Oxidizing properties:	Not determined.	
Vapor pressure:	Not determined.	
Density:		
Relative density:	0.83	
Vapor density:	Not determined.	
Evaporation rate:	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/water):	: Not determined.	
· Viscosity		
Dynamic:	Not determined.	
Kinematic at 40 °C (104 °F):	12 mm²/s	
Other information	No relevant information available.	

10 Stability and reactivity

- · **Reactivity:** No relevant information available.
- · Chemical stability: Stable under normal temperatures and pressures.
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

Possibility of hazardous reactions

Reacts with strong oxidizing agents.

Toxic fumes may be released if heated above the decomposition point.

Reacts with certain metals.

- · Conditions to avoid Excessive heat.
- · Incompatible materials Oxidizers
- · Hazardous decomposition products Carbon monoxide and carbon dioxide

(Cont'd. on page 6)

Page: 6/9

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 29, 2017 Revision: November 29, 2017

Trade name: Tap Magic Aluminum Liquid

(Cont'd. of page 5)

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

64742-47-8 Distillates (petroleum), hydrotreated light

Oral LD50 >5000 mg/kg (rat)
Dermal LD50 >2000 mg/kg (rabbit)

- Primary irritant effect:
- · On the skin: Based on available data, the classification criteria are not met.
- · On the eye: Based on available data, the classification criteria are not met.
- Sensitization: Contains Cinnamal. May produce an allergic reaction.
- IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Ingestion.

Inhalation.

Eye contact.

Skin contact.

- Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Based on available data, the classification criteria are not met.
- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- · STOT-single exposure: Based on available data, the classification criteria are not met.
- · STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: May be fatal if swallowed and enters airways.

12 Ecological information

- · Toxicity
- · Aquatic toxicity

111-82-0Aliphatic Organic Ester

LC50 0.423 mg/l (fish)

EC50 0.283 mg/l (daphnia)

- Persistence and degradability The product is partially biodegradable. Significant residuals remain.
- · Bioaccumulative potential: No relevant information available.
- Mobility in soil: No relevant information available.
- Additional ecological information
- · General notes: Avoid transfer into the environment.
- Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Cont'd. on page 7)

Page: 7/9

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 29, 2017 Revision: November 29, 2017

Trade name: Tap Magic Aluminum Liquid

(Cont'd. of page 6)

· **vPvB:** Not applicable.

· Other adverse effects No relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Contact waste processors for recycling information.

Smaller quantities can be disposed of with household waste.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- Uncleaned packagings
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information	
· UN-Number · DOT, ADR, IMDG, IATA	UN3082
· UN proper shipping name · DOT, ADR, IMDG, IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Aliphatic Organic Ester)
· Transport hazard class(es)	
· DOT, IMDG, IATA	
· Class · Label	9 Miscellaneous dangerous substances and articles 9
· ADR	
1 1 1 1 1 1 1 1 1 1	
· Class	9 (M6) Miscellaneous dangerous substances and articles
· Label	9
· Packing group · DOT, ADR, IMDG, IATA	III
· Environmental hazards · Marine pollutant:	Yes (DOT) Symbol (fish and tree)
	(Cont'd. on page 8)

Page: 8/9

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 29, 2017 Revision: November 29, 2017

Trade name: Tap Magic Aluminum Liquid

	(Cont'd. of page 7)
Special precautions for user	Warning: Miscellaneous dangerous substances and articles
· Danger code (Kemler): · EMS Number:	90 F-A,S-F
Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	Not regulated when carried in single or combination packaging containing a net quantity of 5 L or less for liquids or 5 kg or less for solids per the following: DOT: 171.4(c)(2) ADR: SP 375 IMDG: 2.10.2.7 IATA: special provision A197
DOT	Labeling as a Marine Pollutant is only required for bulk single package shipments. Bulk packaging consists of a maximum capacity of greater than 450 L (119 gallons) for a liquid and a maximum net mass greater than 400 kg (882 pounds) for a solid. (See 171.4(c))

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- SARA
- · Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

TSCA (Toxic Substances Control Act)

All ingredients are listed.

- · Proposition 65 (California)
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

(Cont'd. on page 9)

Page: 9/9

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 29, 2017 Revision: November 29, 2017

Trade name: Tap Magic Aluminum Liquid

(Cont'd. of page 8)

None of the ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

Canadian Domestic Substances List (DSL):

All ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Date of preparation / last revision November 29, 2017 / -

Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistant, Bio-accumulable, Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Skin Sens. 1: Skin sensitisation - Category 1

Asp. Tox. 1: Aspiration hazard - Category 1

Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com